

C65-8602 al com

23002

SID 63-143-5

ACTUAL WEIGHT AND BALANCE REPORT

COMMAND MODULE FOR LAND AND WATER IMPACT CONTRACT 9-150

BOILERPLATE NO. 2

(U)

4.5.4.5

ISSUED 12 JUNE 1963



WEIGHT CONTROL GROUP

tion ecting the national defense of the factor of the Espionage Laws. Title 18 U.S.C. and the contents in any is prohibited by law. This document contains
United States within the
Section 793 and 794. Its
manner to an unauthor

NORTH AMERICAN AVIATION, INC. SPACE and INFORMATION SYSTEMS DIVISION CLASSIFICATION CHANGE

UNCLASSIFIED

Classified Document Master By authority Changed by

Scientific and Technical Information Facility

Control Station







TABLE OF CONTENTS

| | ITEM | PAGE |
|------|-----------------------------------------------|------|
| I. | INTRODUCTION | 1 |
| II. | WEIGHT, CENTER OF GRAVITY AND INERTIA SUMMARY | 2 |
| III. | ACTUAL WEIGHT AND BALANCE, BOILERPLATE NO. 2 | 3 |





ACTUAL WEIGHT AND BALANCE REPORT

FOR

BOILERPLATE NO. 2

COMMAND MODULE FOR LAND AND WATER IMPACT

INTRODUCTION

Boilerplate No. 2 Command Module actual weight and balance determination was conducted by the Apollo Weight Control Group personnel at the Space and Information Systems Division of North American Aviation, Inc. The proceeding took place on May 17, 1963.

The Weight, Balance and Inertia Summary presents data for the lunar mission—earth landing condition. This condition simulates the Command Module weight and center of gravity with the forward heat shield jettisoned and all chutes, drogue, pilot and main, deployed.

Additional actual weight and balance determinations will be made in the field at various times and will be incorporated as an appendix to this report.



WEIGHT, CENTER OF GRAVITY AND INERTIA SUMMARY


COMMAND MODULE FOR LAND AND WATER IMPACT

BOILERPLATE NO.

| ~ | _ | * |
|------------------------------|-----------|--------------------------------|
| LUG FT.2 | ZAW (Z | 2967 |
| MOMENT OF INERTIA(SLUG FT.2) | (х) нотта | 3329 |
| MOMENT OF | ROLL (X) | 4341 |
| /ITY* | Zв | 7.7 |
| CENTER OF GRAVITY* | Ya | -0•1 |
| CENTE | Ха | 1039.6 -0.1 |
| WEIGHT | | 7840 |
| ITEM | | TOTAL COMMAND MODULE AT IMPACT |

*Centers of gravity are in the NASA reference system except that the longitudinal has an origin 998.7 inches below the tangency NOTE:

of the Command Module structure mold line.



| *Weight of fwd. | fittings | deducted | from average | reading | (35 1he) | |
|-----------------|----------|-----------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|
| - + - A | | AUGUE VOL | TIOM GLASIERS | COMPANY OF THE PARTY OF THE PAR | 1 37 11192.1 | |

| | | | | | ALANCE 2 | سان بالمال الحال الحال المالية ا | | | | |
|----------------------|------------------|---------------------------------------|------------------|----------------|------------------|-----------------------------------------------------------------------------------------------------------------------------|---------|-------|---------|--|
| DESCRIPTION | AVER. READING | ± corr. | WEIGHT | LONG. | MCM. | LAT. | MOM. | VERT. | MOM. | |
| Fred Jack Position G | 1818 1795 | <u> 6</u> | * 1812 * 1799 | | 142876 141851 | 4.15 | 7466 | 0 | 0 | |
| Aft Jack Position B | | -15 | 2628 | 27.02 | 71009 | | | 75.84 | -199308 | |
| Aft Jack Position | 3322 | + 8 | 3113 3330 | 27.02 27.02 | 89977 | 76.12 | 236962 | 76.08 | 253346 | |
| GROSS (as weighed) | | 0 + B [†] +D [†] | 2828 7770 | 27.02 39.11 | 76413 303862 | -76.12 | -215267 | 6.95 | 54038 | |
| conce (ma nerfiller) | TOTAL F | +A+C | 7740 | 39.07 | 302377 | 3.77 | 29161 | | | |

Transfer to Vehicle Reference Axes

$$Y = (LATERAL ARM)(cos 29°- 4¹) - (VERTICAL ARM)(sin 29°- 4¹)$$

$$Z = (LATERAL ARM)(sin 29^{\circ}-4^{\circ}) + (VERTICAL ARM)(cos 29^{\circ}-4^{\circ})$$

$$I = (3.77)(.87406) - (6.95)(.48583) = ____08$$

 $I = (3.77)(.48583) + (6.95)(.87406) = ___7.91$

| DESCRIPTION | WEIGHT | X | WX | Y | WY | Z | WZ |
|--------------------------------|--------|--------------|--------|----|------|------|--------|
| TRANSFERRED CROSS (as weighed) | 7755 | 39.09 | 303120 | 08 | -620 | 7.91 | 61.342 |
| LESS: Aft Fittings | - 47 | 27.0 | -1269 | 85 | 40 | 55 | 26 |
| PLUS: Ballast | 52 | 88.5 | 4602 | 0 | 0 | 27.5 | 1430 |
| Splash Fairing | 10 | 21.0 | 210 | 0 | 0 | | |
| Wiring | 45 | 52.0 | 2340 | 0 | 0 | 50.0 | -2250 |
| Battery | 15 | 43.5 | 652 | 0 | 0 | 7.0 | 105 |
| Camera | 10 | 50 .0 | 500 | 0 | 0 | -8.0 | - 80 |
| CORRECTED WEIGHT AND C.G. | 7840 | 39.6 | 310155 | 07 | -580 | 7.73 | 60573 |